



## MDS Exterior Swing Door Specs for Units

### Swing Door Curtain

1. 26ga grade 80 steel
2. Finish: Sunset Orange, Super Durable Polyester Paint
3. Lock , Chateau Model C-485B-BK-SGL
4. Bottom bar 26ga galvalume with bulb astragal
5. Door stiles, top & bottom cap 20ga galvalume
6. Door stiles are manufactured using a box design for added strength and rigidity
7. Latch side door style is a one piece manufactured component with a continuous striker plate as part of the design for added security
8. X bracing 1" x 1" 20ga galvanize square tubing keeps door from flexing, eliminating sharp edges
9. 3 Button hinges—non-removable pin—per door (screws only; no pop rivets)

### Swing Door Z Frame

1. 20ga galvanized
2. Finish: Sunset Orange Super Durable Polyester Paint
3. Fastened to existing door frame w/ # 8 x ½ tek screws
4. Z frame fastened inside and outside for security
5. Continuous overlapping style

### Drip Ledge

1. 20ga galvanized
2. Finish: Sunset Orange, Super Durable Polyester Paint
3. 3/4" x 1" to cover total length of frame
4. Fastened to top Z frame with #8 x ½ tek screws and caulked

### Wind Chain

1. Attached to existing frame and to swing door with #8 x ½" tek screws

## SDS Exterior Swing Door Specs for Building Entrances

### Swing Door Curtain

1. 24 ga 2-1/2" flat slat; grade 40 steel
2. Finish: Tan, grey, white or bronze as standard; custom colors available for an additional fee
3. Lock , Simplex or Passage style
4. Bottom bar aluminum with bulb astragal
5. Door stiles, top & bottom cap 20ga galvalume
6. Door stiles are manufactured using a box design for added strength and rigidity
7. Lock side door style is a one piece manufactured component with a continuous striker plate as part of the design for added security
8. X bracing 1" x 1" 20ga galvanize square tubing keeps door from flexing, eliminating sharp edges
9. Continuous aluminum hinge

### Swing Door Z Frame

1. 20 ga galvanized mounting angles
2. Finish: 24 ga Z frame to match door color (tan, grey, white or bronze)
3. Fastened to existing door frame w/ # 8 x ½ tek screws
4. Z frame fastened inside and outside for security
5. Continuous overlapping style

### Drip Ledge

1. Finish: 24 ga to match door color
2. 3/4" x 1" to cover total length of frame
3. Fastened to top Z frame with #8 x ½ tek screws and caulked

### Door Closure

1. Attached to existing frame and to swing door with #14 x 1" tek screws





# JANUS

INTERNATIONAL

