

DOOR COMPARISON CHART

Model Number	650	650NS	750	850	850S	850IM	1000	1100	1850	1850IM	1950	1950HD	2000	2500	3100	3100IM	3400	3652
Maximum Width	10′	10′	10′	8′ 8″	12′	8′ 8″	12′	12′	12′	12′	12′	12′	12′	18′	20′	16'	12′	18′
Maximum Height	10′	10′	10′	12′	12′	12′	14′	14′	14′	14′	14′	14′	16′	18′	18′	18'	16′	14′
Application	\Diamond	lack	\Diamond	\Diamond	lack	\uparrow	П	П	П	П	П	Ш	П		П	П	П	
Wind Load Rated	×	×	a	M	1	1	×	a	1	AP .	×	×	×	×	1	1	and the second	1
Barrel	9-1/2"	9-1/2"	9-1/2"	9-½"	9-½"	9-1/2"	9-1/2"	9-½"	9-½"	9-½"	9-1/2"	9-1/2"	12"	12"	12"	12"	12"	12"
Guide	2"	2"	2" WL 2-¼"	4"	4"	4"	2-1/4"	2-1/4"	4"	4"	2-1⁄4"	4"	2-1/4"	4"	4"	4"	4"	2"
Guide Gauge	18-ga	18-ga	18-ga WL 16-ga	wL 12-ga	<mark>wL</mark> 12-ga	WL 12-ga	16-ga	wL 16-ga	wL 16-ga	w∟ 16-ga	16-ga	12-ga	16-ga	12-ga	WL 12-ga	WL 12-ga	wL 12-ga	WL 14-ga
Reduced-Drive Chain Hoist Standard Over 10'w or 10'h	×	×	×	Ø	Ø,	Ø	Ø	Ø,	Ø,	Ø	Ø,	8	Ø	Ø	Ø	Ø	Ø	⊗
Factory Installed Brackets	✓	✓	✓	×	×	×	✓	✓	×	×	×	×	×	×	×	×	×	×
Warranty	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year	1-Year
Impact Rated	×	×	×	✓	×	✓	×	×	×	✓	×	×	×	×	×	✓	✓	×
Color Options	All	All	All	White Only	All	All	All	All	All	All	All	All	All	All	All	All	White Only	All
Vision Panels Optional	×	×	×	×	×	×	×	×	×	×	×	×			×	×	×	×
Insulation Optional	✓	~	✓	✓	~	✓	✓	✓	✓	✓	~	✓	✓	✓	✓	✓	✓	✓
Corrugated Curtain Gauge	26-ga	26-ga	26-ga	24-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	26-ga	24-ga	26-ga

>> Chart Key



Self-Storage/Light Duty

Carports

Barns

Sheds








Freight Terminals



Windlock





JanusIntl.com

HEADQUARTERS

Janus International Group 135 Janus International Blvd. Temple, GA 30179