## **NOTES** 1. OPERATION TYPE MAY BE PUSH-UP, HAND CHAIN OR ELECTRIC 2. FOR CRITICAL FITS DUE TO REDUCED AVAILABLE HEADROOM OR SIDEROOM CLEARANCES, CONSULT FACTORY - 6½" **-**3. THE AXLE CAN BE "TRIMMED" TO ACCOMMODATE LOW SIDEROOM 4. CLEARANCES SHOWN ARE MAXIMUMS. LESSER CLEARANCES MAY BE POSSIBLE. UNLESS OTHERWISE NOTED, DOORS SHALL BE PROVIDED WITH SLIDE LOCKS AT EACH END OF BOTTOM BAR, ENGAGING GUIDES IN THE LOCKED POSITION. 6. ALL OPENING PREPARATION, ELECTRICAL POWER AND FIELD PAINTING SHALL BE PROVIDED BY OTHERS. UP1 SMALL MOUNTING PLATE CURTAIN SERIES 3652I IS AN INSULATED SERIES 3652. (INSTALL ON BOTH JAMBS FOR BRACKET ATTACHMENT TO STEEL JAMBS OF METAL BUILDINGS) 8. CURTAIN FINISH SHALL BE SILICONE POLYESTER PRE-PAINT OVER GALVANIZED GRADE 80 STEEL 2 1/4" 9. GUIDES, BRACKETS, BOTTOM BAR ANGLE AND HEAD STOPS ARE ZINC COATED. 10. MAXIMUM OPENING SIZE: 18'-0" X 14'-0" 11. JANUS MODEL 3652 IS A STATE OF FLORIDA APPROVED WINDLOAD PRODUCT. PRODUCT EVALUATIONS AND STAMPED DRAWINGS ARE ACCESSIBLE VIA. www.floridabuilding.org . FL#21450 12. JANUS PRODUCTS PRODUCED WITH A THIRD-PARTY EVALUATION TO ADHERE TO THE TEXAS DEPARTMENT OF INSURANCE STEEL JAMBS CONCRETE/FILLED BLOCK JAMBS STANDARDS WILL BE LISTED VIA. $\underline{\text{WWW.TDI.TEXAS.GOV}}$ (USING 1/4-14 X 1" SELF-DRILLING SCREW) (USING 1/4" X 3" DEWALT SCREW BOLT +) 13. RAIN LIP CLEARANCE DIMENSION OUTSIDE OF GUIDE = 4 \(\frac{1}{32}\)" MINIMUM (\*) FOR PUSH-UP OPERATION. 14 GA GUIDE MOUNTING DETAIL DIMENSIONS VARIES PER OPENING WIDTH FOR HAND CHAIN OPERATION.... FOR ELECTRIC OPERATION..... BRACKET ATTACHMENT ≤ 7' OPENING WIDTH. > 7' - ≤ 9' OPENING WIDTH... CONCRETE/FILLED BLOCK: WEDGE-BOLT+, % " X 1 % " LONG STEEL: HEX BOLT, GR.5, % " - 16" X 1 % " LONG, & % " - 16" GR.2 LOCKNUT .7 23/32 FOR OUTSIDE OF CHAIN DRIVE... STEEL JAMB THICKNESS FASTENER SPACING > 9' - ≤ 18' OPENING WIDTH. NOTE: RIGHT SIDE DRIVE SHOWN BARREL ASSEMBLY HORIZONTAL 14 GA (.075") 4.00" O.C. MAX HEADROOM OPENING WIDTH 5.00" O.C. MAX 12 GA (.105") VERTICAL 3/16" (.188") 8.00" O.C. MAX HEAD STOP - BRACKET **HEADROOM REQUIRED OPENING** VERTICAL HORIZONTAL RAIN LIP DETAIL HEIGHT HEADROOM HEADROOM **GUIDE** THRU 8'-0" 20" 20" OPENING - SLIDE LOCK 21" 21" THRU 10'-0" HEIGHT 21 ½" 21" THRU 14'-0" **BOTTOM BAR ASSEMBLY** 26 GA CURTAIN PANEL DETAIL DRAWING #: 814011-0000

COMMERCIAL DOOR SERIES: 3652 / 3652I CUSTOMER NUMBER: DATE:

CURTAIN

3 1/4"

DETAIL A

DETAIL A

770-562-2850 FAX: 770-562-2264

CUSTOMER NAME: CONTACT: SLIDE LOCK **INSIDE ELEVATION** END VIEW **BOTTOM BAR ASSEMBLY** PROJECT NAME: JAMB TYPE OPERATION WEATHERSTRIP OPENING SIZE FACTORY OUTSIDE PROJECT LOCATION: CURTAIN PUSH UP OPERATION QTY ORDER ADDED OPTIONS REDUCED HAND **ELECTRIC** TOP HEADER SIDE NUMBER WIDTH HEIGHT CHAIN PLANT: SALESPERSON: DRAWN BY DATE: JANUS INTERNATIONAL GROUP, LLC. 135 JANUS INTERNATIONAL BLVD. DRAWING NUMBER: SHT: OF: TEMPLE, GA 30179-4435