## **HEADROOM REQUIRED**


OPENING HEIGHT	VERTICAL HEADROOM	HORIZONTAL HEADROOM
THRU 8'-0"	19"	19"
OVER 8'-0" THRU 10'-0"	20"	20"
OVER 10'-0" THRU 12'-0"	20-1/2"	20"

## BRACKET ATTACHMENT

CONCRETE/MASONRY: WEDGE-BOLT+, 3/8" X 1-3/4" LONG STEEL: HEX BOLT GR.5, %"-16 X 1-¼" LONG, & %"-16 LOCKNUT WOOD: LAG SCREW, %" X 3" LONG



- 2. FOR CRITICAL FITS DUE TO REDUCED AVAILABLE HEADROOM OR SIDEROOM CLEARANCES, CONSULT FACTORY
- 3. CLEARANCES SHOWN ARE MAXIMUMS, LESSER CLEARANCES MAY BE POSSIBLE
- 4. UNLESS OTHERWISE NOTED, LOCKING SHALL BE BY SINGLE MINI LATCH BOLTED TO CURTAIN AND SUITABLE FOR DOUBLE PADLOCKS AND SINGLE CYLINDER LOCK, BY OTHERS
- 5. LATCH COVER IS YELLOW ZINC (STAINLESS STEEL, OPTIONAL) AND SLIDE IS MAGNETIC STAINLESS
- CURTAIN FINISH SHALL BE SILICONE POLYESTER PRE-PAINT OVER GALVANIZED GRADE 80 6. STEEL
- 7. GUIDES, BRACKETS, BOTTOM BAR ANGLE AND HEAD STOPS ARE ZINC COATED
- MAXIMUM OPENING SIZE: 8'-8" X 12'-0" 8.
- JANUS MODEL 850S IS A MIAMI DADE COUNTY APPROVED WINDLOAD PRODUCT. PRODUCT 9. EVALUATIONS AND STAMPED DRAWINGS ARE ACCESSIBLE AT www.miamidade.gov (FL#21450)
- 10. PRODUCTS PRODUCED WITH A THIRD-PARTY EVALUATION TO ADHERE TO THE TEXAS DEPARTMENT OF INSURANCE STANDARDS WILL BE LISTED AT www.tdi.texas.gov
- 11. MINIMUM RAIN-LIP CLEARANCE DIMENSION OUTSIDE EACH GUIDE = 6-<sup>1</sup>/<sub>4</sub>" for STEEL JAMBS & 7-5/16" - CONCRETE / FILLED BLOCK JAMBS



Π

MINI LATCH

OUTSIDE OF DOOR VIEW

8"

0

0

 $\longrightarrow$ 

UP↑

\_\_\_\_

10"

MINI LATCH CYLINDER

LOCK BACK PLATE

(ONLY USED WITH CYLINDER LOCK)

LARGE MOUNTING PLATE

DRAWN BY:

DRAWING NUMBER:

20"

