DOMINATOR™
EASYROLLER 14

SUITABLE FOR USE ON ROLLING SHEET DOORS

YOUR 'GO TO' ROLLING DOOR OPENER

Our flagship rolling door opener, the Dominator EasyRoller 14™ features a slim profile, reliability, security and convenience. The slim-fit chassis suits low side room installations.

The Dominator EasyRoller 14™ incorporates bright LED courtesy lighting. The opener comes with Soft Start/Soft Stop operation, advanced door profiling and obstruction sensing for secure and safe operation. The Service Indicator lets you know when it is time to service your door. EasyRoller 14™ is suitable for use on doors up to 14ft.

WHAT'S IN THE BOX:

Opener with LED Courtesy Light

Wireless wall button and Two TrioCode™ 128 Remote Controls

Safety Beams

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode™ *128* remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.

*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

KEY FEATURES

- 600N DC Motor
- Soft Start / Soft Close
- Slim fit design
- LED Courtesy Light
- Intelligent Safety System

INTELLIGENT SAFETY SYSTEM (ISS)

If contact is made with an obstruction while moving, the opener either stops or reverses the door to reduce the risk of injury or property damage.

SOFT START / SOFT CLOSE

The Soft Start / Soft Close feature ramps speed up and down at the start and end of each cycle, therefore reducing stress on the door and opener.

SMART SIMPLE SECURE

Power	Input Voltage	120 Vac / 60Hz
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Short-Term Lifting Force	600N
Installation[1,2]	Door Size (approx.)	180 ft²
	Door Height (max)[3]	14 ft
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	2 x LED
	Safety Beam Compatibility	2-wire Safety Beams
	Drum Wheel Adaptor	Suits most doors*
Warranty[4]	5 year/10,000 cycles on parts[4] 1 year on accessories	

Suits most rolling sheet doors. Not suitable for rolling steel doors

OPTIONAL ACCESSORIES

Wireless Keypad Weather resistance, secure access without a transmitter or keys is great for school kids and active families.

[1] Windy conditions can activate the obstruction feature of the opener.
[2] Suitable for use on dead axle doors.
[3] Max height 14ft on a door with a 12" drum wheel. Less opening height on a door with a 9.5" drum wheel.
[4] Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.

Member of:

IDA — International Door Association — Enhancing the Value and Professionalism of Door & Access Systems Dealers

Member DASMA — Door & Access Systems Manufacturers Association International

FC

ETL c us — Intertek

SAFETY & SECURITY FEATURES

Soft Start/Soft Close

Intelligent Safety System

Door Profiling

128 TrioCode™ *128*

POWER & MOUNTING SYSTEMS

DC Motor

OPERATING MODES & FEATURES

LED Courtesy Lights

Auto Close

Service Indicator

Vacation Mode

AUX Auxiliary Output

See our website for our icon glossary explanations.

SMART SIMPLE SECURE

For more information on this door opener and other Automatic Technology products please visit us online at www.ata-america.com

automatic TECHNOLOGY | JANUS INTERNATIONAL GROUP